

Tectyl[®]
PROTECTIVE PRODUCTS



JUNE 2006

Valvoline EMEA
P.O. Box 421
2990 AK Barendrecht
The Netherlands
T. +31 (0)10 497 5000
F. +31 (0)10 497 5955

www.valvolineurope.com

Tectyl[®]
PROTECTIVE PRODUCTS



Customer solutions for
After Market



| Product | Remarks / Film Type / Film Appearance | Recommended Minimum (dry) Film Thickness Microns | Comments |
|---------|---------------------------------------|--|----------|
|---------|---------------------------------------|--|----------|

Non Solvent Based

| | | | |
|--------------|--------|----|--------------------------------|
| TECTYL 4D750 | RESIN. | 40 | PROTECTION OF HOLLOW SECTIONS. |
| TECTYL 4D800 | RESIN. | 40 | PROTECTION OF HOLLOW SECTIONS. |

Solvent Based

| | | | |
|------------------|--|-------|---|
| TECTYL 120 | BITUMEN. WAX. FIRM. BRONZE. | 250 | UNDERBODY COATING TRUCKS AND BUSES. ABRASION RESISTANT. DUAL COAT WITH TECTYL 558-AMC. |
| TECTYL 120-EH | BITUMEN. WAX. THIXOTROPIC. FIRM. BRONZE. | 250 | SAME AS 120 BUT HIGHER FILM BUILD. |
| TECTYL 121-LV | BITUMEN. WAX. THIXOTROPIC. FIRM. BLACK. | 250 | UNDERBODY COATING TRUCKS AND BUSES. ABRASION RESISTANT. INDUSTRIAL OVENS AND CHIMNEYS. |
| TECTYL 122-A | BITUMEN. WAX. THIXOTROPIC. SEMI-FIRM. BLACK. | 250 | UNDERBODY COATING. |
| TECTYL 125 | THIXOTROPIC. SEMI-FIRM. BLACK. | 200 | REPAIR UNDERBODY COATING AFTERMARKET. LOW VISCOSITY. |
| TECTYL 190 BLACK | RESIN. PIGMENT. THIXOTROPIC. FIRM. BLACK. | 250 | PROTECTION AGAINST CORROSION AND ABRASIVE DAMAGE OF FERROUS METALS CAN BE PAINTED OVER. |
| TECTYL 190 GREY | RESIN. PIGMENT. THIXOTROPIC. FIRM. GREY. | 250 | PROTECTION AGAINST CORROSION AND ABRASIVE DAMAGE OF FERROUS METALS CAN BE PAINTED OVER. |
| TECTYL 210-R | WAX. OIL. THIXOTROPIC. SOFT AMBER. | 50 | PROTECTION OF SEAMS, JOINTS AND CREVICE LOCATIONS OF VEHICLES, LESS. |
| TECTYL 210-AM | WAX. OIL. THIXOTROPIC. SOFT AMBER. | 50 | PROTECTION OF SEAMS, JOINTS AND CREVICE LOCATIONS OF VEHICLES, LESS, LOW VISCOSITY. |
| TECTYL 550-ML | WAX. OIL. FIRM. AMBER. TRANSPARENT. | 50 | PROTECTION OF SEAMS, JOINTS AND OTHER CREVICE LOCATIONS OF VEHICLES. |
| TECTYL 558-AMC | WAX. OIL. THIXOTR. SEMI-FIRM. AMBER, TRANSP. | 50 | PROTECTION OF SEAMS, JOINTS AND OTHER CREVICE LOCATIONS OF VEHICLES. DUAL COAT WITH TECTYL 120. |
| TECTYL ML WAX | WAX. THIXOTROPIC. SEMI-FIRM. AMBER, TRANSP. | 40-50 | USED TO PROTECT HOLLOW SECTIONS. ROLLING EQUIPMENT AND SPARE PARTS. |
| TECTYL BODYSAFE | BITUMEN. WAX. THIXOTROPIC. SEMI-FIRM. BLACK. | 250 | UNDERBODY COATING AFTERMARKET. |

Waterborne

| | | | |
|---------------|--|--|---|
| TECTYL 5638-W | RESIN. PIGMENT VIBR. DAMPING HARD. BLACK. | 1-2 times substry thickness | USED FOR SOUND DAMPING OF METAL SURFACES. |
| TECTYL 5750-W | BITUMEN. PIGMENT THIXOTROPIC. HARD. DARK GREY. | 350 (500 micron for application in wheel arches) | UNDERBODY COATING. |

