

Tectyl[®]
PROTECTIVE PRODUCTS



JUNE 2006

Valvoline EMEA
P.O. Box 421
2990 AK Barendrecht
The Netherlands
T. +31 (0)10 497 5000
F. +31 (0)10 497 5955

www.valvolineurope.com

Tectyl[®]
PROTECTIVE PRODUCTS



Customer solutions for
General Industry



Product	Remarks / Film Type / Film Appearance	Estimated duration of protection Indoors (or Undercover) and outdoors in months													Recommended Minimum (dry) Film Thickness Microns	Military	Powerplants	Spare parts	General Industry	Comments
		3	6	9	12	15	18	21	24	27	30	33	36	39						

Non Solvent Based

TECTYL 4D800	RESIN.														Outdoor protection is not required	40	●		●	PROTECTION OF HOLLOW SECTIONS.
TECTYL 435-D	WAX, HOTMELT, FIRM, TAN.															38	●		●	PROTECTION OF HIGH-PRECISION OPERATED COMPONENTS.
TECTYL 477-D	OIL, CONCENTRATE, OIL, AMBER, TRANSPARENT.														Depending on concentration	10 (10% in oil)			●	PRESERVATION OF METAL COILS.
TECTYL 800-D	OIL, THIN OILY, TRANSPARENT.															7	●		●	PROTECTION AND LUBRICATION OF PNEUMATIC TOOLS AND LIGHT MACHINERY.
TECTYL 802-A	OIL, TRANSPARENT.															10	●			USED TO PROTECT APPLICATION EQUIPMENT ASSEMBLIES.
TECTYL 810	OIL, CONCENTRATE, THIN OILY, TRANSPARENT.															1,25 (10% in water)	●			WATER DILUTABLE RUST PREVENTATIVE FOR METAL WORKING PROCESSES.
TECTYL 858-F	GREASE, AMBER.															NA	●			USED FOR LUBRICATION AND SURFACE CORROSION PROTECTION OF GROUND VEHICLES AND EQUIPMENT BETW. -54 - +204°C.
TECTYL 859-B	OIL, VCI, TRANSPARENT.															4,3	●	●	●	PRESERVATIVE ADDITIVE FOR ENCLOSED SYSTEMS WHERE VOLATILE COMPONENTS PROVIDE PROTECTION ABOVE THE OIL LEVEL. CAN BE USED AS A CONTACT PRESERVATIVE.
TECTYL 900	OIL, THIN OILY, TRANSPARENT.															5	●	●	●	PROTECTION AND LUBRICATION OF LIGHT WEAPONS, PNEUMATIC TOOLS AND LIGHT MACHINERY.
TECTYL 910	OIL, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●		●	INTERNAL PRESERVATION COMBUSTION ENGINES, MEETS CORROSION PROPERTIES MIL-PRF-21260 GRADE 10.
TECTYL 915W40	OIL, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●		●	INTERNAL PRESERVATION COMBUSTION ENGINES, MEETS CORROSION PROPERTIES MIL-PRF-21260 GRADE 15W40.
TECTYL 930	OIL, THIN OILY, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●		●	INTERNAL PRESERVATION COMBUSTION ENGINES, MEETS CORROSION PROPERTIES MIL-PRF-21260 GRADE 10.
TECTYL 910-E	OIL, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●			INTERNAL PRESERVATION COMBUSTION ENGINES, APPROVED FOR SPECIFICATION: MIL-PRF-21260E GRADE 10.
TECTYL 915W40-E	OIL, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●			INTERNAL PRESERVATION COMBUSTION ENGINES, APPROVED FOR SPECIFICATION: MIL-PRF-21260E GRADE 15W-40.
TECTYL 930-E	OIL, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●			INTERNAL PRESERVATION COMBUSTION ENGINES, APPROVED FOR SPECIFICATION: MIL-PRF-21260E GRADE 15W-40.
TECTYL 940-E	OIL, TRANSPARENT.														Internal Combustion Oil (5 yr. storage)	10	●			INTERNAL PRESERVATION COMBUSTION ENGINES, APPROVED FOR SPECIFICATION: MIL-PRF-21260E GRADE 15W-40.

Solvent Based

TECTYL 120	BITUMEN, WAX, FIRM, BRONZE.															250	●			UNDERBODY COATING TRUCKS AND BUSES. ABRASION RESISTANT. DUAL COAT WITH TECTYL 558-AMC.
TECTYL 120-EH	BITUMEN, WAX, THIXOTROPIC, FIRM, BRONZE.															250	●			SAME AS 120 BUT HIGHER FILM BUILD.
TECTYL 121-LV	BITUMEN, WAX, THIXOTROPIC, FIRM, BLACK.															250		●	●	UNDERBODY COATING TRUCKS AND BUSES. ABRASION RESISTANT. INDUSTRIAL OVENS AND CHIMNEYS.
TECTYL 122-A	BITUMEN, WAX, THIXOTROPIC, SEMI-FIRM, BLACK.															250		●		UNDERBODY COATING.
TECTYL 127-CGW	WAX, PIGMENT, THIXOTROPIC, FIRM ALUMINIUM.															200		●	●	LONG TERM PROTECTION OF METAL SURFACES AGAINST CORROSION IN MOIST AND SALT ATMOSPHERES.
TECTYL 130-AL	WAX, PIGMENT, THIXOTROPIC, FIRM ALUMINIUM.															200		●	●	LONG TERM PROTECTION OF METAL SURFACES AGAINST CORROSION IN MOIST AND SALT ATMOSPHERES.
TECTYL 130-RB	WAX, RED PIGMENT, THIXOTROPIC.															200		●	●	LONG TERM PROTECTION OF METAL SURFACES AGAINST CORROSION IN MOIST AND SALT ATMOSPHERES.
TECTYL 132 BLACK	WAX, PIGMENT THIXOTROPIC, FIRM, BLACK.															250		●	●	PROVIDES OUTSTANDING LONG TERM PROTECTION IN TROPICAL AND INDUSTRIAL ENVIRONMENT.
TECTYL 275	OIL, THIN OILY, TRANSPARENT.															5	●		●	PROTECTION FOR INDUSTRIAL PARTS AND TRANSPORTATION COMPONENTS.
TECTYL 283-S-17	OIL, THIN OILY, TRANSPARENT.															1,5			●	PROTECTION FOR INDUSTRIAL PARTS.
TECTYL 366	RESIN, OIL, SOFT, YELLOW.															45			●	USED TO PROTECT FERROUS AND NON FERROUS PARTS E.G. TOOLS.
TECTYL 400-C	WAX, FIRM, AMBER, TRANSPARENT.															25			●	LONG TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES E.G. TOOLS, SPARE PARTS ETC.
TECTYL 472	OIL, THIN OILY, TRANSPARENT.															3		●	●	PROTECTION FOR INDUSTRIAL PARTS (AFTER PROCESSING WITH CUTTING FLUID).
TECTYL 502-C	OIL, WAX, GREASY, AMBER, TRANSPARENT.															25	●		●	PROTECTION OF FERROUS AND NON-FERROUS PARTS, GEAR WHEELS AND BEARINGS.
TECTYL 502-C-EH	OIL, WAX, GREASY, AMBER, TRANSPARENT.															40			●	PROTECTION OF FERROUS AND NON-FERROUS PARTS, GEAR WHEELS AND BEARINGS.
TECTYL 506	WAX, FIRM, AMBER, TRANSPARENT.															50			●	LONG TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES E.G. TOOLS, SPARE PARTS ETC.
TECTYL 506-G	WAX, FIRM, AMBER, TRANSPARENT.															50			●	LONG TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES E.G. TOOLS, SPARE PARTS ETC.
TECTYL 506-EH	WAX, FIRM, AMBER, TRANSPARENT.															50			●	LONG TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES E.G. TOOLS, SPARE PARTS ETC.
TECTYL 506-WD	WAX, FIRM, AMBER, TRANSPARENT.															50			●	LONG TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES E.G. TOOLS, SPARE PARTS ETC.
MULTIPURPOSE 506	WAX, FIRM, AMBER, TRANSPARENT.															50			●	LONG TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES E.G. TOOLS, SPARE PARTS ETC.
TECTYL 511-M	OIL, WAX, AMBER, TRANSPARENT.															8	●		●	INTERIM PROTECTION OF FERROUS AND NON FERROUS SPARE PARTS.
MULTIPURPOSE 511-M	OIL, WAX, AMBER, TRANSPARENT.															8			●	INTERIM PROTECTION OF FERROUS AND NON FERROUS SPARE PARTS DURING SHIPMENT OR STORAGE.
TECTYL 511-M/HK2	OIL, WAX, AMBER, TRANSPARENT.															4			●	SHORT TERM PROTECTION OF FERROUS AND NON FERROUS SPARE PARTS DURING SHIPMENT OR STORAGE.
TECTYL 518-SUPERWAX	WAX, THIXOTROPIC, SEMI-FIRM, AMBER, TRANSP.															40-50			●	USED TO PROTECT HOLLOW SECTIONS, ROLLING EQUIPMENT AND SPARE PARTS.
TECTYL SUPERWAX ML	WAX, THIXOTROPIC, SEMI-FIRM, AMBER, TRANSP.															40-50			●	USED TO PROTECT HOLLOW SECTIONS, ROLLING EQUIPMENT AND SPARE PARTS.
TECTYL 542	WAX, FIRM, AMBER, TRANSPARENT.															15			●	PROVIDES MEDIUM TERM INDOOR AND OUTDOOR PROTECTION OF METALLIC SURFACES.
TECTYL 550-ML	WAX, OIL, FIRM, AMBER, TRANSPARENT.															50			●	PROTECTION OF SEAMS, JOINTS AND OTHER CREVICE LOCATIONS OF VEHICLES.
TECTYL 558-AMC	WAX, OIL, THIXOTR. SEMI-FIRM, AMBER, TRANSP.															50	●		●	PROTECTION OF SEAMS, JOINTS AND OTHER CREVICE LOCATIONS OF VEHICLES. DUAL COAT WITH TECTYL 120.
TECTYL 846	WAX, FIRM, AMBER, TRANSPARENT.															50	●		●	EXCELLENT PROTECTION OF MACHINERY, PARTS, TOOLS AND TUBING.
TECTYL 846-K-19	WAX, FIRM, AMBER, TRANSPARENT.															50	●		●	USED TO PROTECT MACHINERY AND PARTS DURING SHIPMENT OR STORAGE.
TECTYL 891-D CLASS 1	BITUMEN, FIRM, BLACK.															64	●		●	PROTECTION OF NON-PRECISION PARTS, EXTERIOR SURFACES.
TECTYL 894-D CLASS 1	WAX, SEMI-FIRM, AMBER, TRANSPARENT.															18	●		●	MEDIUM TERM INDOOR AND SHORT TERM OUTDOOR PROTECTION OF METALLIC SURFACES AFTER MACHINE OPERATIONS.
TECTYL 1079	WAX, FIRM, LIGHT TAN, TRANSPARENT.															20			●	TO PROTECT PAINTED SURFACES AGAINST WEAR DURING TRANSPORTATION AND STORAGE.
TECTYL 1422-S BLACK	RESIN PIGMENT, HARD, BLACK.															65-75			●	TO PROTECT INERMODAL CHASSIS, FARM, ROAD AND CONSTRUCTION EQUIPMENT.

Waterborne

TECTYL 300 CLEAR	RESIN, CLEAR.															25-50			●	PROTECTION OF CHASSIS DURING OVERSEAS TRANSPORT.
TECTYL 300-G CLEAR	RESIN, CLEAR.															25-50			●	PROTECTION OF CHASSIS DURING OVERSEAS TRANSPORT.
TECTYL 5015-W	LIGHT, FIRM, TRANSCULENT.														under cover and avoiding direct sunlight	40	●	●	●	PROTECTION OF SPARE PARTS, TUBES AND ALL KIND OF MACHINERY DURING STORAGE.
TECTYL 5350-W	LIGHT BROWN, FIRM, WAXY, TRANSLUCENT.														under cover and avoiding direct sunlight	40		●	●	PROTECTION OF FERROUS OBJECTS LIKE FINNED TUBES, STEEL CASINGS, PIPES ETC.
TECTYL 5638-W	RESIN, PIGMENT VIBR. DAMPING HARD, BLACK.															1-2 times substry thickness			●	USED FOR SOUND DAMPING OF METAL SURFACES.
TECTYL 5750-W	BITUMEN, PIGMENT THIXOTROPIC, HARD, DARK GREY.															350 (500 for wheel arches)	●	●	●	UNDERBODY COATING.
V-DAMP 3680	RESIN, PIGMENT VIBR. DAMPING HARD, TAN.															1-2 times substry thickness			●	USED TO PROVIDE SOUND DAMPING OF METAL SURFACES.